



High Voltage Products. High Voltage Experts.

TRIAxIAL HIGH VOLTAGE CABLE

Rated Voltage		Part Number	Conductor Size				Semicon Diameter (mm)	Dielectric		Inner Shield		
DC (kV)	AC (kV)		AWG	Strands	mm ²	Diameter (mm)		Material	Diameter (mm)	Construction	AWG	Semicon
22.5	-	2122	4	30 BC Braids	21.00	23.40	31.10	EPR	41.90	28 TC Braid	4	Tape
40	-	2186	16	19/29 SPC	1.31	1.50	2.50	Silicone	7.50	34 TC Braid	16	Ink & Tape
50	17	2302TNJ	16	19/29 SPC	1.31	1.50	2.50	Silicone	7.50	34 BC Braid	16	Ink & Tape
60	20	2024TVJ	12	19/25 SPC	3.31	2.30	3.40	Silicone	9.10	34 BC Braid	15	Ink & Tape
75	25	2241	14	19/27 SPC	1.94	1.80	2.80	EPR	7.80	2x30 TC Braid	10	Extruded
100	30	2212TVJ	10	76x	4.92	1.30	4.80	EPR	15.70	34 TC Braid	14	Extruded
125	40	2243TPJ	8	49x	8.37	4.20	5.60	EPR	15.70	30 TC Braid	8	Tape
160	50	2042TVJ	11	76x	4.17	1.30	6.10	EPR	24.90	34 TC Braid	15	Extruded
350	-	2068-R2	2	7x	33.62	7.40	7.60	Paper/Oil	23.60	35 x 0.08 Cu	4	Tape