



High Voltage Products. High Voltage Experts.

Pulsed technologies ltd. is a leading global innovation company since 1994

# RU-Series Three-electrode Spark Gaps



- No standby power consumption
- Compact and robust design
- Low cost
- Lifetime over  $10^7$  shots
- Operating temperature -60 to +300°C
- Customized solutions

The range of three-electrode spark gaps offered by PulseTech comprises hermetically sealed gas filled switches available with DC hold-off voltages from 0.5 to 150 kV.

- **Medical lithotripsy**
- **Aircraft engines firing**
- **Peaking circuits**
- **Crowbar protection**
- **General fast high energy switching**

## Absolute (Maximums/Nonsimultaneous) Ratings

Standard models	Operating Range, kV	Maximum charge transfer, mC, repetitive /single discharge	Peak current, kA, repetitive /single discharge	Delay time, $\mu$ sec,	Overall dimensions, $\varnothing$ xH, mm
RU87	0.6 – 10	3/100	1/7	1	22x48
RU83	0.6 – 6	5/200	1/7	0.3	38x32
RU84	1.0 – 15	5/200	1/7	0.3	38x40
RU85	5.0 – 50	5/200	1/7	0.3	38x55
RU86	5.0 – 50	400	15	0.3	65x50
RU89	2.0 – 150	500	15	0.3	52x84
RU90	5.0 – 50	100 000	100	0.3	150x160

### Notes:

- Tubes with various DC hold-off voltage are available. This is signified by numerals following the model type after hyphen, e.g. RU83-7 means that the DC hold-off voltage is 7 kV.
- For use above a specific voltage for each type of spark gaps immersion in insulating media can be recommended.
- The life of a spark gap is governed primarily by the deposition of electrode material on the insulating surfaces. The rate of erosion of the electrodes may be related to peak current as  $\sim (I_{pk})^{1.6}$
- The life of a spark gap also increases with decreasing repetition rate.
- All data and specifications are subject to change without notice.



**pulsetech**  
pulsedtechnologies

Issued May 2012  
ISO certified