

Metglas Inc. "AMCC" to MK Magnetix Inc. Part Number Cross Reference

Hitachi Metgals	MK Magnetix part numbers			MK Magnetix Dimensioning (in.)				Hitachi-Metglas Dimensioning (mm)			
2605SA1 Metglas®	2605SA1 Metglas®	Nanocrystalline M1	Nanocrystalline MB	D strip	E build	F window width	G window height	d strip	a build	b window width	c window height
AMCC-4	SC2105L1	SC2105M1	SC2015MB	0.590	0.354	0.394	1.291	15.0	9.0	10.0	32.8
AMCC-6.3	SC2043L1	SC2043M1	SC2043MB	0.787	0.394	0.433	1.299	20.0	10.0	11.0	33.0
AMCC-8	SC2044L1	SC2044M1	SC2044MB	0.787	0.433	0.512	1.181	20.0	11.0	13.0	30.0
AMCC-10	SC2045L1	SC2045M1	SC2045MB	0.787	0.433	0.512	1.575	20.0	11.0	13.0	40.0
AMCC-16A	SC2047L1	SC2047M1	SC2047MB	0.984	0.433	0.512	1.575	25.0	11.0	13.0	40.0
AMCC-16B	SC2048L1	SC2048M1	SC2048MB	0.984	0.433	0.512	1.969	25.0	11.0	13.0	50.0
AMCC-20	SC2049L1	SC2049M1	SC2049MB	1.181	0.433	0.512	1.969	30.0	11.0	13.0	50.0
AMCC-25	SC2051L1	SC2051M1	SC2051MB	0.984	0.512	0.591	2.205	25.0	13.0	15.0	56.0
AMCC-32	SC2052L1	SC2052M1	SC2052MB	1.181	0.512	0.591	2.205	30.0	13.0	15.0	56.0
AMCC-40	SC2053L1	SC2053M1	SC2053MB	1.378	0.512	0.591	2.205	35.0	13.0	15.0	56.0
AMCC-50	SC2054L1	SC2054M1	SC2054MB	0.984	0.630	0.787	2.756	25.0	16.0	20.0	70.0
AMCC-63	SC2055L1	SC2055M1	SC2055MB	1.181	0.630	0.787	2.756	30.0	16.0	20.0	70.0
AMCC-80	SC2056L1	SC2056M1	SC2056MB	1.575	0.630	0.787	2.756	40.0	16.0	20.0	70.0
AMCC-100	SC2057L1	SC2057M1	SC2057MB	1.771	0.630	0.787	2.756	45.0	16.0	20.0	70.0
AMCC-125	SC2058L1	SC2058M1	SC2058MB	1.378	0.748	0.984	3.268	35.0	19.0	25.0	83.0
AMCC-160	SC2059L1	SC2059M1	SC2059MB	1.575	0.748	0.984	3.268	40.0	19.0	25.0	83.0
AMCC-200	SC2060L1	SC2060M1	SC2060MB	1.969	0.748	0.984	3.268	50.0	19.0	25.0	83.0
AMCC-250	SC2061L1	SC2061M1	SC2061MB	2.362	0.748	0.984	3.543	60.0	19.0	25.0	90.0
AMCC-320	SC2062L1	SC2062M1	SC2062MB	1.969	0.866	1.378	3.346	50.0	22.0	35.0	85.0
AMCC-400	SC2063L1	SC2063M1	SC2063MB	2.559	0.866	1.378	3.346	65.0	22.0	35.0	85.0
AMCC-500	SC2064L1	SC2064M1	SC2064MB	2.165	0.984	1.575	3.346	55.0	25.0	40.0	85.0
AMCC-630	SC2065L1	SC2065M1	SC2065MB	2.756	0.984	1.575	3.346	70.0	25.0	40.0	85.0
AMCC-800A	SC2066L1	SC2066M1	SC2066MB	3.346	0.984	1.575	3.346	85.0	25.0	40.0	85.0
AMCC-800B	SC2067L1	SC2067M1	SC2067MB	3.346	1.181	1.575	3.740	85.0	30.0	40.0	95.0
AMCC-1000	SC2068L1	SC2068M1	SC2068MB	3.346	1.299	1.575	4.134	85.0	33.0	40.0	105.0

Our Amorphous 2605SA1 & Nanocrystalline cut cores—a step above the rest:

- Superior bond strength.
- 180C continuous operating temperature
- Proprietary processes peak magnetic performance and increased interlaminar resistance for minimal high frequency losses
- Drop-in replacement for Metglas Inc. cores. Manufactured to meet or exceed Metglas Inc.'s standards.
- **Custom Core lead times typically 3-4 weeks! Full line of Metglas AMCC equivalent sized parts usually in stock.**

Customizable To Meet Your Needs

- Available in c-cores, e-cores, toroids, bars, etc.
- Custom shapes & sizes, from several grams to 1800kg+
- Multiple cuts when airgap distribution is required
- Tighter dimensional tolerances and magnetics when required
- Call for more details about these and other possibilities

