

K-SERIES K400



RF PEAK POWER UP TO 60 MW

MODULATOR PEAK POWER UP TO 160 MW

This high-end solid-state pulse modulator is designed to handle a wide range of large klystrons with a RF peak power from 30 MW to 60 MW. ScandiNova offers everything from a standard modulator to a turn-key RF system that includes all necessary system components from the wall socket to the accelerator, such as the klystron, diagnostics and low-level RF. Review our other pulse modulators in the modular K-Series.

EXCELLENCE IN PULSED POWER

SYSTEM SPECIFICATIONS	UNIT	DATA	NOTES
Klystron RF Peak Power	MW	30–60	Depends on choice of klystron
Klystron RF Average Power	kW	40	Maximum
Modulator Peak Power	MW	160	Maximum
Modulator Average Power	kW	125	Maximum
Pulse Voltage	kV	280–450	Typical range
Pulse Current	A	230–450	Typical range
Pulse Repetition Frequency Range	Hz	0–500	Typical range. Depending on max average power (see options).
Pulse Length, Top	µs	0.5–15	Typical range. Depending on max mod. power.
Flatness (Voltage)	%/µs	< 0.5	Flat top. Depending on load (see options).
Modulator Voltage Stability, RMS	%	0.01	(see options)
Cooling (incl. RF parts)	l/min	15-210	Clean water

INTERFACE	DEFAULT	OPTION
Mains Power, 3 Phase	400 VAC, 50/60 Hz	208/380/480 VAC
Mains Power, Single Phase	230 VAC, 50/60 Hz	115 VAC
Control Interface	ModBus TCP	
Water Cooling Interface In/Out	ISO G2"	
Trig Input	Electrical and Optical	
Diagnostics	Pulse Voltage and Current	See Options

Standard Modulator Includes

Control System (ScandiCat)
Remote Control
Local Control Panel
Mains Power Distribution
Cooling System
Filament PS
Klystron Socket
Pulse Sensors
Hard Wired Interlock System

Additional System Components

Low Level RF Amplifier/Generator
Circulator & RF Loads
Directional Coupler
Waveguide Windows
Vacuum PS
Solenoid PS
Klystron
Extended cooling for Klystron,
Solenoid etc.

Typical Klystron Loads

CPI	Toshiba	SLAC
VKS-8262P1	E3729 (70 MW)	XL-4
VKX-8311	E3730A	XL-5
	E3735A	
Thales	E3748 (E37202)	
TH2100B		
TH2128C		
TH2128D		
TH2158		
TV2022A		

Options

Pulse/RF Diagnostics
Enhanced PRF Range (up to 1000 Hz)
Enhanced Stability (down to 0.002%)
Enhanced Flatness (<0.25 %/µs)
Neutron Resistant Switching

Size and Weight

Weight approx. 2600 kg
(excl. oil, klystron, solenoid)
Oil volume approx. 950 l

*Information contained in this document
is subject to change without notice.*

