



1HVFK SERIES

5 to 50kV, 700 to 900mA, 150nS Recovery
Rectifier Blocks with Insert Mounting



Features

- Epoxy Molded Encapsulation with Mounting Inserts
- Threaded Brass Solder Terminal Inserts


Specifications¹

Part Number	V_{RRM} V	I_{FAVM} mA	V_F V	I_R μA	I_{FSM} A	T_{RR} nS	L in.
1HVF5K	5000	900	8	0.5	50	150	2.5
1HVF8K	8000	900	12	0.5	50	150	3.5
1HVF10K	10000	900	15	0.5	50	150	3.5
1HVF15K	15000	900	24	0.5	50	150	5
1HVF20K	20000	700	30	0.5	50	150	5
1HVF25K	25000	700	40	0.5	50	150	6
1HVF30K	30000	700	48	0.5	50	150	6
1HVF40K	40000	700	60	0.5	50	150	7
1HVF50K	50000	700	78	0.5	50	150	7

Temperature °C	
Storage Temperature	-55 to 150
Maximum Junction Temperature	150

¹25°C ambient temperature unless stated otherwise.

Drawings



Dimensions in inches, tolerances ± 0.020 except as noted

Specification Definitions

Specifications		Conditions
V_{RRM}	Maximum Repetitive Reverse Voltage	-
I_{FAVM}	Maximum Average Forward Current	At $T_A = 55^\circ C$
V_F	Maximum Forward Voltage Drop	At I_{FAVM}
I_R	Maximum Leakage Current	At V_{RRM}
I_{FSM}	Maximum Surge Current	At 8.3 mS, Single Half Sine
T_{RR}	Maximum Reverse Recovery Time	$I_F = 0.5 I_{FAVM}$; $I_R = -I_{FAVM}$; $I_{RR} = -0.25 I_{FAVM}$

Note: Specifications subject to change without notice. Photo is representation only.

