

ARTESYN LCM300

300 Watts Bulk Front End



Advanced Energy's Artesyn LCM300 series provide for a very wide range of AC-DC embedded power requirement. Featuring high build quality with robust screw terminals, long life, and typical full-load efficiency of greater than 91 percent, these units are ideal for use in industrial and medical applications. They are backed by a comprehensive set of industrial and medical safety approvals and certificates. Variable-speed 'Smart Fans' draw on software controls developed by Advanced Energy to match fan speed to the unit's cooling requirement and load current. Slowing the fan not only saves power but also reduces wear, thus extending its life.

AT A GLANCE

Total Power

300 W

Input Voltage

85 to 264 VAC

of Outputs

Single

SPECIAL FEATURES

- 310 W output power (360 W at 45°C for 24 V and 36 V models)
- Low cost
- 1.61" x 4.0" x 7.0"
- 7.1 W/in³
- Industrial/Medical safety
- -40°C to 70°C with derating
- Optional 5 V @ 2 A housekeeping
- High efficiency: 91% @ 230 VAC
- Variable speed "Smart Fans"
- DSP controlled
- Conformal coat option
- Wide adjustment range
- Margin programming
- OR-ing FET
- PMBus compliant

Compliance

- EMI Class B
- EN61000 Immunity
- RoHS 3
- PMBus

SAFETY

- UL62368-1 1598/1433 60601-1 Ed 3
- CSA 62368-1
- TUV 62368-1 60601-1
- China CCC
- CB Scheme Report/Cert
- CE and UKCA Mark


* Note: LCM300 tested according to the medical standard IEC 60601-1-2 4th Edition.



ELECTRICAL SPECIFICATIONS

Input	
Input range	90 to 264 VAC (Operating) 115/230 VAC (Nominal) TERMINAL BLOCK
Frequency	47 to 63 Hz, Nominal 50/60
Input fusing	Internal 8 A fuses, both lines fused
Inrush current	≤ 20 A peak, cold start at 25°C
Power factor	0.98 typical, meets EN61000-3-2
Harmonics	Meets IEC61000-3-2 requirements
Input current	5 Arms max input current, at 90 VAC
Hold up time	20 ms minimum for main O/P, at full rated load
Efficiency	> 91% typical at full load / 230 VAC nominal
Leakage current	< 0.3 mA at 240 VAC
Power line transient	MOV directly after the fuse
Isolation	Isolation: PRI-Chassis 2500 VDC Basic PRI-SEC 4000 VAC Reinforced 2xMOPP SEC-Chassis 500 VDC

LCM300Q Efficiency Without the 5 Vsb



ELECTRICAL SPECIFICATIONS (CONTINUED)

Output		
Output rating	See table 1	90 to 264 VAC
Set point	± 0.5%	90 to 264 VAC
Total regulation range	Main output ± 2% 5V VSB 4.8 to 5.4V	Combined line/load/transient when measured at output terminal
Rated load	310 W (360 W for current Q and U variants)	Derate linear to 50% from 50°C to 70°C
Minimum load	Main output @ 0.0 A 5V VSB @ 0.0 A	No loss of regulation
Output noise (PARD)	1% max p-p 100 mV max p-p	Main output 5V VSB output Measured with a 0.1 µF Ceramic and 10 µF Tantalum Capacitor on any output, 20 MHz
Output voltage overshoot		No overshoot/undershoot outside the regulation band during on or off cycle
Transient response	< 300 µSec	50% load step @ 1 A/µs Step load valid between 10% to 100% of output rating Recovery time to within 1% of set point at onset of transient
Max units in parallel		Up to 10
Short circuit protection	Protected, no damage to occur	Bounce mode
Remote sense		Compensation up to 500 mV
Forced load sharing	To within 10% of all shared outputs	Analog sharing control
Overload protection (OCP)	105% to 125% 120% to 170%	Main output 5V VSB output
Overvoltage protection (OVP)	125% to 145% 110% to 125%	12 V output 5V VSB output

ENVIRONMENTAL SPECIFICATIONS


Operating temperature	-40°C to +70°C, linear derating to 50% from 50°C to 70°C
Storage temperature	-40°C to +85°C
Humidity	10 to 90%, non-condensing. Operating. Conformal coat option available
Fan noise	< 45 dBA, 80% load at 40°C; Fan Off when unit is inhibited
Altitude	Operating, 10,000 feet (3048 m) Storage, 30,000 feet
Shock	MIL-STD-810F 516.5, Procedure I, VI. Storage
Vibration	MIL-STD-810F 514.5, Cat. 4, 10. Storage

ORDERING INFORMATION

Model Number	Output	Nominal Output Voltage Set Point	Set Point Tolerance	Adjustment Range	Current		Output Ripple P/P (0-50 °C)	Max Continuous Power ¹	Combined Line/Load Regulation
					Min	Max			
LCM300L	12 V	12 V	± 0.5%	9.6 - 14.4 V	0 A	25.0 A	120 mV	310 W	2%
LCM300N	15 V	15 V	± 0.5%	14.25 - 19.5 V	0 A	20.0 A	150 mV	310 W	2%
LCM300Q	24 V	24 V	± 0.5%	19.2 - 28.8 V	0 A	14.5 A	240 mV	360 W	2%
LCM300U	36 V	36 V	± 0.5%	28.8 - 43.2 V	0 A	9.7 A	360 mV	360 W	2%
LCM300W	48 V	48 V	± 0.5%	43.0 - 60.0 V	0 A	6.3 A	480 mV	310 W	2%

Note 1: Max continuous power includes 5 V @ 2 A standby power if the optional standby output is available.

LCMXXXXY	-	A	-	B	-	C	-	###
Case Size		Input Termination		Acoustic Noise		Option Codes		Hardware Code
1-Phase input where XXXX =								
300 = 1.61" x 4.0" x 7.0", 300 W				Blank = Standard		Blank = No Options		Factory Assigned for Modified Standards
		T = Terminal Block				1 = Conformal Coat		
Voltage Code Y =						4 = 5 V Standby		
Code						5 = Opt 1 + 4		
L	12							
N	15							
Q	24							
U	36							
W	48							



Signal Output Signal Connectors (SK2)

SK2 Mating Connector: JST Part Number PHDR-20VS;

Contact Pins: JST Part Number SPHD-001T-P0.5

LED INDICATORS

2 provided are clearly visible up to a 45 degree offset from vertical with office environment ambient lighting. The status is reflected in the indicator color.

The DC_OK LED LED shall light green if the DC output is within specification, and should be off if the output falls out of specification.

The AC_OK LED LED is green if the AC is within specification and off when out of specification. Note: With 5 V standby, Green also indicates that PSU is in standby mode/output off.

CONTROL SIGNALS

AC_OK Open collector 0.5 V maximum at 10 mA. Both emitter and collector access provided.

DC_OK Open collector 0.5 V maximum at 10 mA. Both emitter and collector access provided.

DC_OK will de-assert when output is loss due to OCP, OVP, OTP, or Fan Fault (for -N option).

PS_INHIBIT/ENABLE Signal 0.0 to 0.5 V contact closure, output OFF (output ON for LCM300U-T-4-401).

PIN ASSIGNMENT

Signals	Name Description		Pin Number(s)
+Vout	Power rail		SK4
GND	Power GND		SK5
Signals	Name Description	Amps per pin	Pin Number(s)
A2	EEPROM address		1
-VPROG	Return connection of external supply for Margin Programming		2
A1	EEPROM address		3
-Vsense	Remote sense return		4
ISHARE	Load share voltage		5
A0	EEPROM address		6
SDA1	Serial data signal (I²C)		7
+VPROG	Positive connection of external supply for Margin Programming		8
SCL1	Serial clock signal (I²C)		9
+Vsense	Remote sense positive		10
5VSB	5V standby	2 A	11
GND	5V standby return	2 A	12
5VSB	5V standby	N/A	13
G_DCOK_C	Global DCOK collector		14
GPIOA6	EEPROM write protect		15
G_DCOK_E	Global DCOK emitter (GND)		16
GND	Return ground for output signal and I²C communication		17
G_ACOK_C	Global ACOK collector		18
INH_EN	Turn Off main output		19
G_ACOK_E	Global ACOK emitter (GND)		20

Note: Mating connector for SK2 is:

LANDWIN: PN 2050S2000 Housing and PN 2053T021V Contact

CIVILUX: PN CI0120SD000 Housing and PN CI01TD21PE0 Contact

MECHANICAL DRAWINGS

Weight: 1.76 lbs (0.8 Kg)



MOUNTING LOCATIONS SCREW
PENETRATION DEPTH IS 3.0 mm MAX.

RECOMMENDED SCREW TORQUE:



M3 x 0.5P = 6.4 - 8kgf-cm

M3.5 x 0.6P = 6 - 8kgf-cm


M4.0 x 0.7P = 8 - 10kgf-cm




AIR FLOW DIRECTION




S-M3-OZ1 (8 PLACES)



ACCESSORIES



Order kit part number 73-788-001 for control connector interface with 0.3 m wires attached



Order kit part number 73-788-002 for control connector interface with unloaded housing and 20 pins

MISCELLANEOUS SPECIFICATIONS

Burn-In

100% Burn-in at 45°C, at 80 to 90% load. Duration of burn-in determined by Quality Assurance Procedures.

MTBF

The power supply has a minimum MTBF of 300K hours using the Bell core 332, issue 6 specification @ 25°C and 40°C, ambient, at full load. With the power supply installed in a system in a 25°C ambient environment and operating at full load, capacitor life shall be 5 years at 50°C, minimum for ALL electrolytic capacitors contained within this power supply. The power supply shall demonstrate a MTBF level of > 500,000 hours.

Quality Assurance

Full QAV testing shall be conducted in accordance with Advanced Energy Standards.

Warranty

Advanced Energy shall warrant the power supply to be free of defects in materials and workmanship for a minimum period of three years from the date of shipment, when operated within specifications. The warranty shall be fully transferable to the end owner of the equipment powered by the supply.



For international contact information,
visit advancedenergy.com.

powersales@aei.com (Sales Support)
productsupport.ep@aei.com (Technical Support)
+1 888 412 7832

ABOUT ADVANCED ENERGY

Advanced Energy (AE) has devoted more than three decades to perfecting power for its global customers. AE designs and manufactures highly engineered, precision power conversion, measurement and control solutions for mission-critical applications and processes.

Our products enable customer innovation in complex applications for a wide range of industries including semiconductor equipment, industrial, manufacturing, telecommunications, data center computing, and medical. With deep applications know-how and responsive service and support across the globe, we build collaborative partnerships to meet rapid technological developments, propel growth for our customers, and innovate the future of power.

PRECISION | POWER | PERFORMANCE | TRUST

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2024 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy®, AE® and Artesyn™ are U.S. trademarks of Advanced Energy Industries, Inc.